

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No. 1614.1092

First Named Inventor or Application Identifier:

Makoto SAOTOME et al.

Express Mail Label No.

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

**ADDRESS TO: Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231**

1. ☒ Fee Transmittal Form
2. ☒ Specification, Claims & Abstract [Total Pages: 17]
3. ☒ Drawing(s) (35 USC 113) [Total Sheets: 4]
4. ☒ Oath or Declaration [Total Pages: 3]
 - a. ☒ Newly executed (original or copy)
 - b. ☐ Copy from a prior application (37 CFR 1.63(d)) (for continuation/divisional with Box 17 completed)
 - i. ☐ DELETION OF INVENTOR(S)
Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b).
5. ☐ Incorporation by Reference (usable if Box 4b is checked)
The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.
6. ☐ Microfiche Computer Program (Appendix)
7. ☐ Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
 - a. ☐ Computer Readable Copy
 - b. ☐ Paper Copy (identical to computer copy)
 - c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

8. ☒ Assignment Papers (cover sheet & document(s))
9. ☐ 37 CFR 3.73(b) Statement (when there is an assignee) [] Power of Attorney
10. ☐ English Translation Document (if applicable)
11. ☐ Information Disclosure Statement (IDS)/PTO-1449 [] Copies of IDS Citations
12. ☐ Preliminary Amendment
13. ☐ Return Receipt Postcard (MPEP 503) (Should be specifically itemized)
14. ☐ Small Entity Statement(s) [] Statement filed in prior application, status still proper and desired.
15. ☒ Certified Copy of Priority Document(s) (if foreign priority is claimed)
16. ☐ Other:

17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:[] Continuation [] Divisional [] Continuation-in-part (CIP) of prior application No: / **18. CORRESPONDENCE ADDRESS**

21171

PATENT TRADEMARK OFFICE

**NEW APPLICATION
FEE TRANSMITTAL**

Attorney Docket No. 1614.1092

Application Number

Filing Date

November 7, 2000

AMOUNT ENCLOSED

\$ 750.00

First Named Inventor

Makoto SAOTOME et al.

FEE CALCULATION (fees effective 10/01/97)

CLAIMS	(1) FOR	(2) NUMBER FILED	(3) NUMBER EXTRA	(4) RATE	(5) CALCULATIONS
	TOTAL CLAIMS	14 - 20 =	0	X \$ 18.00 =	\$ 0.00
	INDEPENDENT CLAIMS	1 - 3 =	0	X \$ 80.00 =	0.00
	MULTIPLE DEPENDENT CLAIMS (any number; if applicable)			+ \$240.00 =	0.00
	BASIC FILING FEE				710.00
	Total of above Calculations =				\$ 710.00
	Surcharge for late filing fee, Statement or Power of Attorney (\$130.00)				+ 0.00
	Reduction by 50% for filing by small entity (37 CFR 1.9, 1.27 & 1.28).				- 0.00
	TOTAL FILING FEE =				\$ 710.00
	Surcharge for filing non-English language application (\$130.00; 37 CFR 1.52(d))				+ 0.00
	Recordation of Assignment (\$40.00; 37 CFR 1.21(h)(1))				+ 40.00
	TOTAL FEES DUE =				\$ 750.00

METHOD OF PAYMENT

- ☒ Check enclosed as payment.
- ☐ Charge "TOTAL FEES DUE" to the Deposit Account No., below.
- ☐ No payment is enclosed and no charges to the Deposit Account are authorized at this time.

GENERAL AUTHORIZATION

- ☒ If the above-noted "AMOUNT ENCLOSED" is not correct, the Commissioner is hereby authorized to credit any overpayment or charge any additional fees necessary to:

Deposit Account No.

19-3935

Deposit Account Name

STAAS & HALSEY LLP

- ☒ The Commissioner is also authorized to credit any overpayments or charge any additional fees required under 37 CFR 1.16 (filing fees) or 37 CFR 1.17 (processing fees) during the prosecution of this application, including any related application(s) claiming benefit hereof pursuant to 35 USC § 120 (e.g., continuations/divisionals/CIPs under 37 CFR 1.53(b) and/or continuations/divisionals/CPAs under 37 CFR 1.53(d)) to maintain pendency hereof or of any such related application.

SUBMITTED BY: STAAS & HALSEY LLP


Typed Name

H. J. Staas

Reg. No.

22,010

Signature



Date

November 7, 2000

SPECIFICATION

TO ALL WHOM IT MAY CONCERN:

BE IT KNOWN THAT WE, Makoto Saotome, a citizen of Japan residing at Kawasaki, Japan and Nobuhide Maruo, a citizen of Japan residing at Kawasaki, Japan have invented certain new and useful improvements in

COMMUNICATION DEVICE

of which the following is a specification : -

TITLE OF THE INVENTION

COMMUNICATION DEVICE

BACKGROUND OF THE INVENTION

5 This application claims the benefit of a Japanese Patent Application No.2000-156441 filed May 26, 2000, in the Japanese Patent Office, the disclosure of which is hereby incorporated by reference.

10 1. Field of the Invention

The present invention generally relates to communication devices, and more particularly to a communication device which has a function of controlling a disconnection of a line which is being used for a communication when an abnormality is detected in a computer equipment which is coupled to the communication device.

2. Description of the Related Art

In a communication using a communication device such as a modem which is coupled to or built into a computer equipment, control related to disconnection of a line which is being used for the communication is in most cases carried out based on a signal received from the computer equipment. For this reason, if a failure or the like occurs in the computer equipment and a line disconnection instruction is not correctly issued from the computer equipment, the line remains in a connected state. When the line remains in the connected state, the accounting continues to be made with respect to the use of the line and the connection to a destination. Recently, there are more occasions to make a communication using a combination of the computer equipment, the communication device and a wireless telephone set. Consequently, in addition to the problem of the continued accounting being made when the failure is generated in the computer

With respect to the above described
5 problems, a first method has been proposed to
disconnect the line by detecting a no-communication
state which is generated when an abnormality is
occurs in the computer equipment. However,
according to this first method, the no-communication
10 state is not necessarily caused by the abnormality
state of the computer equipment, and it is difficult
to accurately detect the abnormal state of the
computer equipment. As a result, there is a high
possibility that an unwanted disconnection of the
15 line will be made.

25 As described above, it is conventionally impossible to disconnect the line by accurately detecting the abnormal state of the computer equipment using a simple structure or, to disconnect the line by accurately detecting the abnormal state of the computer equipment without the need to modify the existing hardware and software of the computer equipment.

35 Accordingly, it is a general object of the
present invention to provide a novel and useful
communication device in which the problems described

Another and more specific object of the present invention is to provide a communication device which can disconnect a line by accurately
5 detecting an abnormal state of a computer equipment, without having to modify existing hardware and software of the computer equipment, and by use of a simple structure.

The signal peculiar to the USB may be selected from a group of a frame start (SOF) signal, an interrupt transfer request signal, a control transfer signal and a bulk IN transfer request signal.

Other objects and further features of the
30 present invention will be apparent from the
following detailed description when read in
conjunction with the accompanying drawings.

35 FIG. 1 is a system block diagram showing a
first embodiment of a communication device according
to the present invention;

FIG. 3 is a diagram for explaining the first embodiment; and

5

DESCRIPTION OF THE PREFERRED EMBODIMENTS

10

15

20

30

35

5 The USB 4 is a standardized serial bus
which connects a personal computer and a peripheral
equipment thereof. By transmitting signals using
the USB 4, it is possible to manufacture the
peripheral equipment at a low cost. Hence, existing
10 personal computers employ the USB 4 as a standard,
as an external bus. This embodiment effectively
utilizes the USB 4.

In order to detect a change of state of the communication device 1, the host unit 2 issues an interrupt transfer request with respect to the communication device 1 at predetermined time intervals. The interrupt transfer request is made by transmitting an interrupt transfer request signal to the communication device 1 via the USB 4. This interrupt transfer request signal is peculiar to the USB 4. An interrupt transfer is made when periodically transferring small amounts of data from

the communication device 1 to the host unit 2. For example, the change information stored in the internal buffer is transferred from the communication device 1 to the host unit 2 by the interrupt transfer. Because of the structure of the USB 4, a data transfer cannot be started from the communication device 1 even in the case of the interrupt transfer. The data transfer is started by a polling operation which is carried out by the host unit 2 to determine whether or not data to be transferred to the host unit 2 exists within the communication device 1.

The communication device 1 constantly monitors the existence of the interrupt transfer request made via the USB 4. More particularly, the interrupt detector 13 detects the interrupt transfer request signal which is received via the USBIF 11. When a detected time interval of the interrupt transfer request signal is within a detection time interval which is preset in the timer 14, the interrupt detector 13 judges that the operation of the host unit 2 is normal, and the communication via the line which is connected to the wireless telephone set 3 is continued. In this case, the data received via the USB 4 are transferred to the wireless telephone set 3 via the USBIF 11, the data controller 12 and the data line 5-1. In addition, the command received via the USB 4 is transferred to the wireless telephone set 3 via the USBIF 11, the line controller 15 and the command line 5-2. Furthermore, the control signal received via the USB 4 is transferred to the wireless telephone set 3 via the USBIF 11, the line controller 15 and the control line 5-3.

On the other hand, when the detected time interval of the interrupt transfer request signal is longer than the detection time interval preset in

09706854.110700

the timer 14, the interrupt detector 13 judges that the operation of the host unit 2 is abnormal, and the line controller 15 forcibly ends the communication by disconnecting the line which is connected to the wireless telephone set 3. The line can be disconnected by a line disconnecting method which supplies a line disconnect instruction to the wireless telephone set 3 or a line disconnecting method which cuts OFF a power supply of the wireless telephone set 3. The connection of the line which is being used for the communication can be disconnected by supplying a command or a control signal for disconnecting the line from the line controller 15 to the wireless telephone set 3 via the command line 5-2 or the control line 5-3. In this case, it is possible to prevent the accounting from being continued unnecessarily with respect to the use of the line and the connection to a destination. In addition, the power supply of the wireless telephone set 3 can be cut OFF by supplying the command or the control signal for cutting OFF the power supply from the line controller 15 to the wireless telephone set 3 via the command line 5-2 or the control line 5-3. In this case, it is not only possible to prevent the accounting from being continued unnecessarily with respect to the use of the line and the connection to the destination, but it is also possible to prevent unnecessary wear of a battery of the wireless telephone set 3.

FIG. 2 is a flow chart for explaining the operation of this first embodiment. In FIG. 2, a step S1 sets an upper limit value of the timer 14, and sets the line disconnecting method which is to be employed. A step S2 starts a communication via the wireless telephone set 3 based on a communication request signal from the host unit 2, and starts a count of the timer 14. A step S3

decides whether or not a counted value of the timer 14 exceeds the set upper limit value . If the decision result in the step S3 is NO, a step S4 counts up the counted value of the timer 14. A step 5 S5 decides whether or not an interrupt transfer request is issued with respect to a concerned end point. The end point refers to a part forming an information source or sink during the communication between the host unit 2 and the communication device 10 1. The process returns to the step S3 if the decision result in the step S5 is NO. On the other hand, if the decision result in the step S5 is YES, a step S6 clears the counted value of the timer 14, and the process returns to the step S3. In addition, 15 if the decision result in the step S3 is YES, a step S7 disconnects the line which is being used for the communication, and the process ends.

The signal peculiar to the USB 4 is of course not limited to the interrupt transfer request signal, and other signals such as a frame start (SOF) signal, a control transfer signal and a bulk IN transfer request signal may be used. The SOF signal is a packet which is issued from the host unit 2 for every $1.0 \text{ ms} \pm 0.05\%$, for example, and indicates the start of each frame. This SOF signal is not issued with respect to a specific communication device or end point, but is issued periodically if the host unit 2 has an appropriate configuration. On the other hand, the control transfer signal is issued when using a control transfer mode in which the communication device 1 transfers configuration information thereof or the like to the host unit 2 and the host unit 2 transfers configuration information thereof or the like to the communication device 1, and also when transferring a small amount of data. The control transfer signal corresponds to a standard device

request or the like which is defined by the USB 4,
and thus, the control transfer mode is supported
without exception by any unit or device which
supports the USB 4. In addition, even in the case
5 of a request other than the standard device request,
it is possible to use a vendor request as the
control transfer signal to have a peculiar meaning.

When using the bulk IN transfer, it is
possible to use the bulk IN transfer request signal
10 similarly to the interrupt transfer request signal
described above.

When using the SOF signal as the signal
peculiar to the USB 4, it is possible to detect the
abnormality related to the hardware of the host unit
15 such as the cutting OFF of the power supply of the
host unit 2. In addition, when using the interrupt
transfer request signal or the control transfer
signal as the signal peculiar to the USB 4, it is
possible to detect the abnormality of the host unit
20 2 such as hang-up which is caused by software,
because both the interrupt transfer and the control
transfer are not only dependent on the hardware of
the host unit 2 but are also dependent on the
operation of the application software 21 and the
25 driver software 22 for carrying out the
communication. The above described signals peculiar
to the USB 4 are not implemented exclusively for
detecting the abnormality of the host unit 2, and
are used during the normal operation of the host
30 unit 2. For this reason, it is unnecessary to
modify the hardware and software of the host unit 2
in order to realize the present invention.

FIG. 3 is a diagram for explaining this
first embodiment. In FIG. 3, those parts which are
35 the same as those corresponding parts in FIG. 1 are
designated by the same reference numerals, and a
description thereof will be omitted. In FIG. 3, a

09706854 110700

connector 42 is provided on one end of a cable 41,
and a connector 43 is provided on the other end of
the cable 41. The connector 42 is connected to a
USB connector of the host unit 2, and the connector
5 43 is connected to a connector of the wireless
telephone set 3. The cable 41 forms the USB 4. In
addition, the communication device 1 shown in FIG. 1
is built into the connector 43. Accordingly, pins
of the connector 43 are provided in correspondence
10 with the data line 5-1, the command line 5-2 and the
control line 5-3. By providing the communication
device 1 within the connector 43, it is possible to
connect the host unit 2 and the wireless telephone
set 3 to the communication device 1 having the
15 function of automatically disconnecting the line, by
simply connecting the host unit 2 and the wireless
telephone set 3 by the cable 41.

FIG. 4 is a diagram for explaining a
second embodiment of the communication device
20 according to the present invention. In FIG. 4,
those parts which are the same as those
corresponding parts in FIG. 3 are designated by the
same reference numerals, and a description thereof
will be omitted. In FIG. 4, a connector 52 is
25 provided on one end of a cable 51, and a connector
53 is provided on the other end of the cable 51.
The connector 52 is connected to a USB connector of
the host unit 2, and the connector 53 is connected
to a connector of the wireless telephone set 3. The
30 cable 51 forms the USB 4. In addition, the
communication device 1 shown in FIG. 1 is built into
the host unit 2 or the wireless telephone set 3. By
providing the communication device 1 within the host
unit 2 or the wireless telephone set 3, it is
35 possible to connect the host unit 2 and the wireless
telephone set 3 to the communication device 1 having
the function of automatically disconnecting the line,

09706554.40700

by simply connecting the host unit 2 and the wireless telephone set 3 by the cable 51.

Next, a description will be given of a third embodiment of the communication device according to the present invention. In this third embodiment, a log storage section is further provided to store a log of the disconnection of the line, in addition to the structure of the first or second embodiment described above. For the sake of convenience, it is assumed in this third embodiment that the log storage section is formed by the internal buffer of the communication device 1. However, it is of course possible to form the log storage section by a memory or the like which is independent from the internal buffer. Moreover, the log storage section may be provided within the host unit 2 or within the wireless telephone set 3. By providing the log storage section and storing the log of the disconnection of the line, it is possible to access the log at an arbitrary time from the host unit 2 or, to automatically access the log and notify the log to the user of the host unit 2.

When restoring the host unit 2, the line controller 15 may re-connect to the line which was disconnected, using the log which is stored in the log storage section.

Next, a description will be given of a fourth embodiment of the communication device according to the present invention. In this fourth embodiment, a notifying section is further provided to notify the disconnection of the line to the host unit 2, in addition to the structure of any one of the first through third embodiments described above. In this fourth embodiment, it is assumed for the sake of convenience that the notifying section is formed by the line controller 15. In other words, the line controller 15 of this fourth embodiment

instructs the disconnection of the line to the wireless telephone set 3, and also notifies the disconnection of the line to the host unit 2 via the USBIF 11 and the USB 4.

5 It is possible to employ a known notifying means when notifying the disconnection of the line to the user of the host unit 2. In other words, the disconnection of the line may be notified to the user by a display output using LED or the like, and
10 an audio output using a buzzer, a melody, voice message or the like. In addition, in a case where an electronic mail function is provided in the wireless telephone set 3 for sending electronic mail, this electronic mail function may be used to notify
15 the disconnection of the line to a manager or the like at a remote location by sending an electronic mail.

 Further, the present invention is not limited to these embodiments, but various variations
20 and modifications may be made without departing from the scope of the present invention.

25

30

35

004074 45890460

WHAT IS CLAIMED IS

5

1. A communication device comprising:
detecting means for detecting a signal peculiar
to a universal serial bus (USB) obtained via the
USB; and

10

disconnecting means for disconnecting a line
which is being used for a communication when the
signal peculiar to the USB is not detected by said
detecting means within a predetermined time.

15

2. The communication device as claimed in
claim 1, wherein the signal peculiar to the USB is
selected from a group of a frame start (SOF) signal,
an interrupt transfer request signal, a control
transfer signal and a bulk IN transfer request
signal.

25

3. The communication device as claimed in
claim 1, wherein said disconnecting means instructs
a disconnection of the line which is being used for
the communication via a command line or a control
line, with respect to a wireless telephone set which
is coupled to the communication device.

35

09706854 410700

5

10

15

20

25

30

35

8. The communication device as claimed in

claim 7, further comprising:

control means for re-connecting to the line
which was disconnected using the log of the
disconnection of the line stored in said log storage
5 means, when restoring a computer equipment which is
coupled to the communication device via the USB.

10

9. The communication device as claimed in
claim 1, wherein said detecting means and said
disconnecting means are built into a connector of a
cable connecting a computer equipment and a wireless
15 telephone set.

20

10. The communication device as claimed
in claim 1, wherein said detecting means and said
disconnecting means are built into one of a computer
equipment and a wireless telephone set which are
coupled via the communication device.

25

11. The communication device as claimed
30 in claim 2, wherein said disconnecting means
instructs a disconnection of the line which is being
used for the communication via a command line or a
control line, with respect to a wireless telephone
set which is coupled to the communication device.

35

00706854.10700

12. The communication device as claimed
in claim 11, wherein said disconnecting means
disconnects the line which is being used for the
communication by cutting OFF a power supply of the
5 wireless telephone set.

10 13. The communication device as claimed
in claim 11, wherein said detecting means and said
disconnecting means are built into a connector of a
cable connecting a computer equipment and a wireless
telephone set.

15

14. The communication device as claimed
20 in claim 11, wherein said detecting means and said
disconnecting means are built into one of a computer
equipment and a wireless telephone set which are
coupled via the communication device.

25

30

35

002074 45890460

ABSTRACT OF THE DISCLOSURE

A communication device is constructed to include a detecting section for detecting a signal peculiar to a universal serial bus (USB) obtained via the USB, and a disconnecting section for disconnecting a line which is being used for a communication when the signal peculiar to the USB is not detected by the detecting section within a predetermined time.

10

15

20

25

30

35

002077-45890260

FIG. 3





FIG. 4



Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Declaration and Power of Attorney For Patent Application

特許出願宣言書及び委任状

Japanese Language Declaration

日本語宣言書

下記の氏名の発明者として、私は以下の通り宣言します。

As a below named inventor, I hereby declare that:

私の住所、私書箱、国籍は下記の私の氏名の後に記載された通りです。

My residence, post office address and citizenship are as stated next to my name.

下記の名称の発明に関して請求範囲に記載され、特許出願している発明内容について、私が最初かつ唯一の発明者（下記の氏名が一つの場合）もしくは最初かつ共同発明者であると（下記の名称が複数の場合）信じています。

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

COMMUNICATION DEVICE

上記発明の明細書（下記の欄でx印がついていない場合は、本書に添付）は、

the specification of which is attached hereto unless the following box is checked:

☐ 月 日 に提出され、米国出願番号または特許協定条約国際出願番号を _____ とし、
(該当する場合) _____ に訂正されました。

☐ was filed on _____
as United States Application Number or
PCT International Application Number
_____ and was amended on
_____ (if applicable).

私は、特許請求範囲を含む上記訂正後の明細書を検討し、内容を理解していることをここに表明します。

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

私は、連邦規則法典第37編第1条56項に定義されるとおり、特許資格の有無について重要な情報を開示する義務があることを認めます。

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

Page 1 of 3

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner of Patents and Trademarks, Washington, DC 20231.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Japanese Language Declaration (日本語宣言書)

私は、米国法典第35編119条(a)-(d)項又は365条(b)項に基づき下記の、米国外の国の少なくとも一カ国を指定している特許協力条約365(a)項に基づく国際出願、又は外国での特許出願もしくは発明者証の出願についての外国優先権をここに主張するとともに、優先権を主張している、本出願の前に出願された特許または発明者証の外国出願を以下に、枠内をマークすることで、示しています。

Prior Foreign Application(s)

外国での先行出願

Pat. Appln. No. 2000-156441	Japan
(Number) (番号)	(Country) (国名)
(Number) (番号)	(Country) (国名)

I hereby claim foreign priority under Title 35, United States Code, Section 119 (a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

Priority Not Claimed

優先権主張なし

26/May/2000
(Day/Month/Year Filed) (出願年月日)
(Day/Month/Year Filed) (出願年月日)

私1、第35編米国法典119条(e)項に基づいて下記の米国特許出願規定に記載された権利をここに主張いたします。

I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.

(Application No.) (出願番号)	(Filing Date) (出願日)
-----------------------------	------------------------

(Application No.) (出願番号)	(Filing Date) (出願日)
-----------------------------	------------------------

私は、下記の米国法典第35編120条に基づいて下記の米国特許出願に記載された権利、又は米国を指定している特許協力条約365条(c)に基づく権利をここに主張します。また、本出願の各請求範囲の内容が米国法典第35編112条第1項又は特許協力条約で規定された方法で先行する米国特許出願に開示されていない限り、その先行米国出願書提出日以降で本出願書の日本国内または特許協力条約国際提出日までの期間中に入手された、連邦規則法典第37編1条56項で定義された特許資格の有無に関する重要な情報について開示義務があることを認識しています。

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s), or 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of application.

(Application No.) (出願番号)	(Filing Date) (出願日)
-----------------------------	------------------------

(Status: Patented, Pending, Abandoned) (現況: 特許許可済、係属中、放棄済)

(Application No.) (出願番号)	(Filing Date) (出願日)
-----------------------------	------------------------

(Status: Patented, Pending, Abandoned) (現況: 特許許可済、係属中、放棄済)

私は、私自身の知識に基づいて本宣言書中で私が行なう表明が真実であり、かつ私の入手した情報と私の信じていることに基づき表明が全て真実であると信じていること、さらに故意になされた虚偽の表明及びそれと同等の行為は米国法典第18編第1001条に基づき、罰金または拘禁、もしくはその両方により処罰されること、そしてそのような故意による虚偽の声明を行えば、出願した、又は既に許可された特許の有効性が失われることを認識し、よってここに上記のごとく宣誓を致します。

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Japanese Language Declaration (日本語宣言書)

委任状: 私は下記の発明者として、本出願に関する一切の手続きを米特許商標局に対して遂行する弁理士または代理人として、下記の者を指名いたします。(弁理士、または代理人の氏名及び登録番号を明記のこと)

James D. Halsey, Jr., 22,729; Harry John Staas, 22,010; David M. Pitcher, 25,908; John C. Garvey, 28,607; J. Randall Beckers, 30,358; William F. Herbert, 31,024; Richard A. Gollhofer, 31,106; Mark J. Henry, 36,162; Gene M. Garner II, 34,172; Michael D. Stein, 37,240; Paul I. Kravetz, 35,230; Gerald P. Joyce, III, 37,648; Todd E. Mariette, 35,269; Harlan B. Williams, Jr., 34,756; George N. Stevens, 36,938; Michael C. Soldner, 41,455; Norman L. Ourada, 41,235; Kevin R. Spivak, P-43,148; and William M. Schertler, 35,348 (agent)

書類送付先

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith (list name and registration number)

Send Correspondence to:

STAAS & HALSEY
700 Eleventh Street, N.W.
Suite 500
Washington, D.C. 20001

直接電話連絡先: (名前及び電話番号)

Direct Telephone Calls to: (name and telephone number)

STAAS & HALSEY
(202) 434-1500

唯一または第一発明者名	Full name of sole or first inventor
	Makoto Saotome
発明者の署名	Inventor's signature
日付	Date
	Makoto Saotome October 27, 2000
住所	Residence
	Kawasaki, Japan
国籍	Citizenship
	Japan
私書箱	Post Office Address
	c/o FUJITSU LIMITED, 1-1, Kamikodanaka 4-chome, Nakahara-ku, Kawasaki-shi, Kanagawa, 211-8588 Japan
第二共同発明者	Full name of second joint inventor, if any
	Nobuhide Maruo
第二共同発明者	Second inventor's signature
日付	Date
	Nobuhide Maruo October 27, 2000
住所	Residence
	Kawasaki, Japan
国籍	Citizenship
	Japan
私書箱	Post Office Address
	c/o FUJITSU LIMITED, 1-1, Kamikodanaka 4-chome, Nakahara-ku, Kawasaki-shi, Kanagawa, 211-8588 Japan

(第三以降の共同発明者についても同様に記載し、署名をすること)

(Supply similar information and signature for third and subsequent joint inventors.)